

KPB 135 Ex manual push button






The flameproof KPB135 manual push button is ATEX / IECEx certified for use in potentially explosive atmospheres. It can be used to activate alarms to alert personnel to potential dangers, help signal the need for immediate action in emergency situations and more. It is constructed from GRP. Optional SIL2 IEC61508 certification.

ATEX / IECEx Certification: ATEX Zone 1 and Zone 2 Certified for group IIB +H2 gas / vapour and Zone 21 and Zone 22 compliant for dust / powder applications.

Application: Oil and gas, chemical, petrochemical, pharmaceutical, marine and offshore applications

Key features: Robust and highly reliable, this Ex manual push button is designed for corrosive environments and hazardous areas. Housing is moulded Glass-Reinforced Polyester (GRP), protected by a paint UV resistant. These ATEX / IECEx compliant manual push buttons are compatible with PLC, ESD and DCS systems.

Options: There are two versions, a push button and push button with key Reset. The visualisation functions, line detection and lift flap protection are optional. A range of accessories is available to customise this ATEX / IECEx manual push button. These include pipe mounting brackets, sunshades, tag and duty labels and other accessories.




KPB 135 Ex manual push button

MATERIAL	• Enclosure: Glass-Reinforced Polyester (GRP)		
COLOUR	• RED : RAL3001/3028 • BLACK : RAL9005 • ORANGE : RAL2010	• YELLOW : RAL1018 • GREEN : RAL6032	• BLUE : RAL5005 • GREY : RAL7038
INGRESS PROTECTION	• IP66/67		
AMBIENT TEMPERATURE FOR OPERATION	• T6 = - 40°C ~ + 55°C , T5 = - 40°C ~ + 60°C, T4 = - 40°C ~ + 70°C		
CERTIFICATION	• ATEX, IECEX		
EX CODE	• II 2 GD Ex d IIC +H2 T6 Gb • Ex tb IIIC T85°C		
STANDARD	• EN / IEC 60079-0, EN / IEC 60079-1, EN / IEC 60079-31		
ATEX AREA ZONE	• Gas zone: 1 & 2 Dust zone: 21 & 22		
AMBIENT HUMIDITY*	• up to 95%		
RATED IMPULSE WITHSTAND VOLTAGE	• 1kV following IEC 61000-4-5		
CONTACT TYPE	• 1x C/O or 2x C/O		
COMMAND TYPE UNIT	• self reset or key push pull		
RATING	• AC 125/250 V (50/60Hz) = 11 A*** ; 30V DC = 6A***; 125 VDC = 0,3A***; 250 V DC = 0,6A***		
MINIMUM VOLTAGE AND CURRENT	• DC 5V 10mA		
SHORTS CIRCUIT PROTECTION	• 10 A gG		
CABLES ENTRY	• 2 x M20, 1 x M25 + 1 x M20, 1 x 1/2" NPT + 1 x M20, 1 x 3/4" NPT + 1 x M20		
TERMINAL	• From 22 to 14 AWG - from 0.50 mm2 to 2.5 mm2		
NET WEIGHT	• 2 Kg		
LINE RESISTOR**	• 470 Ohms**	• 1 watt	
SIGNALLING LED**	• Green U= 24V DC I=10mA; Red U=24V DC I= 20mA		

* = without runoff - ** = optional - *** resistive load - cable gland and blind plug not provided

KPB 135 Ex manual push button

		Product	Certification	Switches	Duty label	Tag label	Reset	LED indicator	Features	Connection	Entry position	Housing
		KPB	135	S	N	Y	K	L	FRD	A	T	RD
PB	= PUSH BUTTON											
135	= HAZARDOUS AREA											
136	= NON-CERTIFIED											
S	= 1											
Y	= YES (SEE LIST)											
N	= NO											
Y	= YES											
N	= NO											
S	= SELF-RESET											
K	= KEY RESET											
L	= RED & GREEN											
R	= RED											
G	= GREEN											
N	= NO LED											



RD		= RED
YW		= YELLOW
BU		= BLUE
BL		= BLACK
GN		= GREEN
GY		= GREY
OJ		= ORANGE
OR		= OTHER
T	= TOP	
B	= BOTTOM	

A = 2 x M20 x 1.5
B = 1 x M25 x 1.5 + 1 x M20 x 1.5
C = 1 x 1/2" NPT + 1 x M20 x 1.5
D = 1 x 3/4" NPT + 1 x M20 x 1.5

Additional adaptors can be supplied as well as blanking plugs and cable glands, see below.

F	= LIFT FLAP
R	= RESISTOR(S)
D	= DIODE(S)
N	= NO FEATURES