


EVA50SS/FLASH DOUBLE OR TRIPLE

zone 1

zone 2

Ex db IIC Gb Ex tb IIIC Db II2GD

T6
T 85°C



zone 21

zone 22

DIRECTIVE 2014/34/UE



LIGHTING FIXTURE
XENON FLASHING LAMP

SEGNALATORE LUMINOSO
LAMPADA XENON

IP66



Stainless Steel 316

Caratteristiche:	Segnalatore luminoso con lampada allo Xenon ad elevato rendimento, sono idonee per la segnalazione ostacoli per camini, ciminiere, fiaccole, campanili, palazzi, gru, ponti, torri radiotelevisive, piloni di teleferiche e linee elettriche, generatori eolici, antenne radar e telecomunicazioni e, nello specifico, per il mondo dell'industria petrolchimica e petrolifera. Certificata INERIS, bassi consumi e durata illimitata. Guarnizione O-RING in neoprene per protezione meccanica IP66. Connessione Direttamente al portalampada L, N, Pe. Sez. max. 4mm2.
Features:	Lighting fixtures with long-life xenon bulb, are ideal for chimneys, towers, smokestacks, bell towers, buildings, cranes, bridges, radio/television masts, cable car and power line pylons, wind turbines, radar and telecommunication antennas and specifically for use in the petrochemical and oil industries. INERIS certificate, low consumption and high performance. Neoprene O-RING gasket for protection IP66. Connection Direct to lamp holder L, N, Pe. Max section 4mm2.
Materiali:	Corpo STAINLESS STEEL 316 , viteria in stainless steel, Vetro borosilicato resistente agli urti ed alle alte temperature sigillato nella ghiera in alluminio, gabbia in acciaio inox (se richiesta).
Materials:	Body STAINLESS STEEL 316 , stainless steel hardware, Shock and temperature resistant borosilicate glass sealed with aluminium shade ring, stainless steel guard (on request).

EVA50SS/FLASH



**EVA50SS/FLASH DL2
(double lamp)**



**EVA50SS/FLASH DL3
(triple lamp)**



Specifica tecnica / Technical specification						
	EVA50SS EVC50SS	SOLO EVC50SS ONLY EVC50SS		EVA50SS EVC50SS		
Tensione / Voltage	12-24 VAC/VDC	48 VAC	48 VDC	110 VAC	110VDC	230 VAC
Corrente / Rated current	300mA			40mA		20mA
Temperatura / Working temperature	-20°C +60°C					
Frequenza / Frequency	50/60HZ					
Assorbimento medio / Power middle	2W		1,8W		4,5W	
Lamp power / Effective Intensity	6J 29Cd					
Flash-minuto / Flash-minut	75 (other to be defined)					
Servizio / Service	Continuo / Continuous					
Colore corpo / Color body	Stainless steel natural / Other color on request					
Imbocchi / Cable entries	EVA50SS 1 x M25x1,5					

COLORI GEMME: **ROSSO - GIALLO - ARANCIO - VERDE - BLU - BIANCO**
Signaling lamps: **Red - yellow - orange - green - blue - white**

